




'Basic' ball valves

Female threaded outlet - Viton - Basic System ITEM 223



REFERENCE	DESCRIPTION	Net weight	Volumen (m ³)	contenido.peso bruto	Unidades lote
1011272	FPM IMPLEX BALL VALVE FEMALE THREAD O. 4"	5.840	0.04460	12.52	2
1011492	FPM BALL V. FEM THREAD OUT. 1/2"	0.154	0.02244	7.20	40
1011493	FPM BALL V. FEM THREAD OUT. 3/4"	0.211	0.02244	8.94	40
1011494	FPM BALL V. FEM THREAD OUT. 1"	0.366	0.03129	11.56	30
1011495	FPM BALL V. FEM THREAD OUT. 1 1/4"	0.626	0.03129	13.09	20
1011496	FPM BALL V. FEM THREAD OUT. 1 1/2"	0.900	0.03129	14.07	15
1011497	FPM BALL V. FEM THREAD OUT. 2"	1.427	0.03682	14.82	10
1011498	FPM BALL V. FEM THREAD OUT. 2 1/2"	2.802	0.03129	11.78	4
1011499	FPM BALL V. FEM THREAD OUT. 3"	4.406	0.02244	9.30	2





ITEM 223 | Female threaded outlet - Viton - Basic System

CÓDIGO	r	DN	PESO (g)	A	B	C	D	E	F	PN	TIPO ROSCA
11492	1/2"	15	154	91	52	17	78	94	47	PN16	BSP
11493	3/4"	20	211	101	59	20	84	100	51	PN16	BSP
11494	1"	25	366	120	70	23	97	140	66	PN16	BSP
11495	1 1/4"	32	626	134	84	26	128	161	72	PN16	BSP
11496	1 1/2"	40	899	153	99	33	142	171	77	PN16	BSP
11497	2"	50	1403	161	121	29	165	182	90	PN16	BSP
11498	2 1/2"	65	2746	204	151	33	222	275	121	PN10	BSP
11499	3"	80	4406	234	175	36	244	290	141	PN10	BSP
11272	4"	100	5840	267	210	42	307	426	155	PN10	BSP





Product Documents



Product Certificates

Company Certificates



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62



tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es