





'Basic' ball valves

Female threaded outlet - 220V electric actuator - PTFE ITEM 252




REFERÊNCIA	DESCRIÇÃO	Peso líquido	Volume (m ³)	contenido.peso bruto	Unidades por lote
1011199	V E MOTOR ACTU 220v S R/H 1/2"	1.554	0.01553	1.79	1
1011200	V E MOTOR ACTU 220v S R/H 3/4"	1.594	0.02244	2.13	1
1011201	V E MOTOR ACTU 220v S R/H 1"	1.073	0.00891	1.26	1
1011202	V E MOTOR ACTU 220v S R/H 1 1/4"	1.940	0.03129	2.50	1
1011203	V E MOTOR ACTU 220v S R/H 1 1/2"	3.090	0.01553	3.42	1
1011204	V E MOTOR ACTU 220v S R/H 2"	3.800	0.02243	4.29	1
1011205	V E MOTOR ACTU 220v S R/H 2 1/2"	6.033	0.03648	6.63	1
1011206	V E MOTOR ACTU 220v S R/H 3"	8.612	0.04460	9.31	1
1011207	V E MOTOR ACTU 220v S R/H 4"	9.286	0.04460	9.98	1








Código	Tamaño	Peso (g)	DN	Actuador	B	C	D	E	F	PN	ROSCA
11199	1/2"	1554	15	H10	17	52	47	91	227	PN16	BSP
11200	3/4"	1594	20	H10	20	59	51	101	232	PN16	BSP
11201	1"	1073	25	H10	23	70	66	120	243	PN16	BSP
11202	1 1/4"	1940	32	S20	26	84	72	134	265	PN16	BSP
11203	1 1/2"	2216	40	S20	33	99	77	153	282	PN16	BSP
11204	2"	3800	50	S20	29	121	90	161	352	PN16	BSP
11205	2 1/2"	4639	65	S35	33	151	121	204	426	PN10	BSP
11206	3"	6335	80	S55	36	175	141	234	450	PN10	BSP
11207	4"	8374	100	S55	42	210	155	267	477	PN10	BSP





Documentación del Producto



Certificados del Producto



Certificados da Empresa

