




'Basic' ball valves

Plain/threaded outlet - PTFE - Basic System ITEM 212

REFERÊNCIA	DESCRIÇÃO	Peso líquido	Volume (m³)	contenido.peso bruto	Unidades por lote
1011160	VALVULA ENLACE MIXTA 20-1/2" PTFE	0.150	0.01553	6.24	40
1011161	VALVULA ENLACE MIXTA 25-3/4" PTFE	0.198	0.02244	8.46	40
1011162	VALVULA ENLACE MIXTA 32-1" PTFE	0.339	0.03129	10.73	30
1011163	VALVULA ENLACE MIXTA 40-1 1/4" PTFE	0.572	0.03129	12.00	20
1011164	VALVULA ENLACE MIXTA 50-1 1/2" PTFE	0.862	0.03129	13.50	15
1011165	VALVULA ENLACE MIXTA 63-2" PTFE	1.383	0.03682	14.38	10
1011166	VALVULA ENLACE MIXTA 75-2 1/2" PTFE	2.670	0.03129	11.24	4
1011167	VALVULA ENLACE MIXTA 90-3" PTFE	4.381	0.02244	9.25	2
1011168	VALVULA ENLACE MIXTA 110-4" PTFE	5.990	0.04460	12.82	2






ITEM 212 | Plain/threaded outlet - PTFE - Basic System

CÓDIGO	f-r	DN	PESO (g)	A	B	C	D	E	F	G	PN	TIPO ROSCA
11160	20-1/2"	15	150	89	52	16	78	92	47	17	PN16	BSP
11161	25-3/4"	20	198	99	59	19	84	92	51	20	PN16	BSP
11162	32-1"	25	339	119	70	23	97	138	66	23	PN16	BSP
11163	40-1 1/4"	32	572	133	84	25	128	160	72	26	PN16	BSP
11164	50-1 1/2"	40	861	151	99	31	142	169	77	33	PN16	BSP
11165	63-2"	50	1382	167	121	38	165	188	90	29	PN16	BSP
11166	75-2 1/2"	65	2670	210	151	45	222	281	121	33	PN10	BSP
11167	90-3"	80	4381	245	175	51	244	301	141	36	PN10	BSP
11168	110-4"	100	5990	288	210	61	307	426	155	42	PN10	BSP





Documentación del Producto



Certificados del Producto



Certificados da Empresa

